

prisma VENT30-C

Invasive and non-invasive ventilation.

With prisma VENT30-C you'll have **mobility and comfort at every level:**

- Pressure range up to 30 hPa
- Use of leakage circuit system (15 mm / 22 mm)
- With autoST mode (autoEPAP, autoF)
- Includes helpful functions for COPD treatment: AirTrap Control, maximum setting for expiratory ramp and Trigger Lockout
- Integrated port for oxygen feed
- Three ventilation programs stored in device memory
- Complete alarm management
- Rechargeable battery with 12-hour capacity
- Easy to use, thanks to intuitive menus, simple operation and quick access ...

... and it's **quiet as a whisper for the well-being and comfort of patients and partners.**

Our Software Solutions



- **prisma CLOUD**
The telemedical connection for experts and patients. Information updated daily on therapy, fully automated, from anywhere.
- **prismaTS**
Therapy software for experts. For detailed data analysis and remote settings.





prisma VENT30-C

Accessories

Humidifier		prismaHYBERNITE	
prisma VENT AQUA	WM 100506	breathing tube, heated	
prismaAQUA	WM 29490	15 mm Ø	WM 29083
		22 mm Ø	WM 29067
Leakage circuit		Inverter	
22 mm Ø, black	WM 23962	24 V	WM 24617
22 mm Ø, autoclavable	WM 24667	12 V	WM 24616
15 mm Ø	WM 29988		

You'll find additional accessories in the prisma VENT accessories catalog. The prisma VENT30-C is compatible with existing prisma VENT accessories.

Technical data

Product Class as per MDR (EU) 2017/745	IIa	Respiratory rate	0 – 60 breaths/min
Dimensions W x H x D in cm	21.8 x 17.5 x 21.8	Target volume	100 ml – 2000 ml
Weight	2.4 kg	Trigger levels	
Weight of internal rechargeable battery (for variant with battery)	0.63 kg	- Inspiration	1 (high sensitivity) to 8 (low sensitivity)
Maximum air flow at 20 hPa	> 220 l/min	- Expiration	95% to 5% of maximum flow in steps of 5%
Operating time of internal rechargeable battery with the following settings: T mode, f = 20 /min, Ti = 1 s, PEEP = 4 hPa, Vt = 800 ml	> 12 h	Pressure increase speed	Level 1: 100 hPa/s Level 2: 80 hPa/s Level 3: 50 hPa/s Level 4: 20 hPa/s
Passive lungs: Resistance R = 5 hPa (l/s); Compliance C = 50 ml/hPa		Pressure decrease speed	Level 1: 100 hPa/s Level 2: 80 hPa/s Level 3: 50 hPa/s Level 4: 20 hPa/s max: maximum slow pressure adjustment
IPAP pressure range	4 – 30 hPa ±1.2 hPa (±8% of setting)	Maximum allowed flow with oxygen feed	15 l/min
PEEP pressure range	4 – 25 hPa ±1.2 hPa (±8% of setting)		

Device description

	Article Nr.
prisma VENT30-C	WM 29360-1110
prisma VENT30-C with integrated rechargeable battery	WM 29370-1110

CE 0197

Please refer to the currently valid price list.



Löwenstein Medical Technology
Kronsaalsweg 40
22525 Hamburg, Germany
T. +49 40 54702-0
F. +49 40 54702-461
info@loewensteinmedical.com

Headquarters
Löwenstein Medical
Arzbacher Straße 80
56130 Bad Ems, Germany
T. +49 2603 9600-0
F. +49 2603 9600-50
info@loewensteinmedical.com
loewensteinmedical.com



© Copyright protected. Reproduction of any type only with express permission from Löwenstein Medical. We are not responsible for printing or typographical errors.

